

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.


[ABOUT DELPHION](#)
[PRODUCTS](#)
[NEWS / EVENT](#)
[MY ACCOUNT](#)
[IP SEARCH](#)
[HELP](#)
[Log Out](#)
[Order Form](#)
[Work Files](#)
[View Cart](#)
[Browse Codes](#)
[IP Listings](#)
[Prior Art](#)
[Derwent](#)
[Advanced](#)
[Boolean](#)
[Quick/Number](#)

The Delphion
Integrated
View

Other Views:

[INPADOC](#)

Title: **JP2001307688A2: PACKING MATERIAL FOR LITHIUM ION BATTERY**

Country: **JP Japan**

Kind: **A2 Document Laid open to Public inspection**

Inventor(s): **YAMASHITA RIKIYA
OKUSHITA MASATAKA
YAMADA KAZUKI
MIYAMA HIROSHI**

Applicant/Assignee:

DAINIPPON PRINTING CO LTD

[Inquire Regarding Licensing](#)

[News, Profiles, Stocks and More about this company](#)

Issued/File Dates: **Nov. 2, 2001 / April 19, 2000**

Application Number: **JP2000000118300**

IPC Class: **H01M 2/02; H01M 10/40;**

Priority Number(s): **April 19, 2000 JP2000000118300**

Abstract:


Problem to be solved: To provide a manufacturing method of a packing material for a lithium ion battery that is used as a material for packing a lithium ion battery, and that has excellent protective physical properties of the lithium ion battery main body and improved productivity in an emboss molding process or the like.

Solution: This packing material for a lithium ion battery is composed of at least a base-material layer, an adhesive layer, aluminum, a conversion treatment layer and a sealant layer, and the resin constituting the sealant layer comprises 0.5 weight % to 10 weight % of one, or two and more of such agents as fluid paraffin, a fatty-acid-ester-system lubricant, a dispersing agent consisting of polyester-system surfactants, and a polyglycerin-ester-system additive. The conversion treatment is potassium chromate treatment, and the resin constituting the sealant layer is random propylene, linear low-density polyethylene and medium-density polyethylene. The sealant layer has a multilayer structure composed of two or more layers, and the innermost resin layer of the sealant layer with the multilayer structure contains the additive.
COPYRIGHT: (C)2001,JPO

Family: [Show known family members](#)

Other Abstract Info: none

Foreign References: No patents reference this one



[View Image](#)

1 page





Nominate this
for the Gallery...

[Subscribe](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [FAQ](#) | [Site Map](#) | [Help](#) | [Contact Us](#)

© 1997 - 2002 Delphion Inc.



(19)

(11) Publication number: **2001307688 A**

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **2000118300**(51) Intl. Cl.: **H01M 2/02 H01M 10/40**(22) Application date: **19.04.00**

(30) Priority:

(43) Date of application
publication: **02.11.01**(84) Designated contracting
states:(71) Applicant: **DAINIPPON PRINTING CO LTD**(72) Inventor: **YAMASHITA RIKIYA
OKUSHITA MASATAKA
YAMADA KAZUKI
MIYAMA HIROSHI**

(74) Representative:

**(54) PACKING MATERIAL
FOR LITHIUM ION
BATTERY**

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a manufacturing method of a packing material for a lithium ion battery that is used as a material for packing a lithium ion battery, and that has excellent protective physical properties of the lithium ion battery main body and improved productivity in an emboss molding process or the like.

SOLUTION: This packing material for a lithium ion battery is composed of at least a base-material layer, an adhesive layer, aluminum, a conversion treatment layer and a sealant layer, and the resin constituting the sealant layer comprises 0.5 weight % to 10 weight % of one, or two and more of such agents as fluid paraffin, a fatty-acid-ester-system lubricant, a dispersing agent consisting of polyester-system surfactants, and a polyglycerin-ester-system additive. The conversion treatment is potassium chromate

treatment, and the resin constituting the sealant layer is random propylene, linear low-density polyethylene and medium-density polyethylene. The sealant layer has a multilayer structure composed of two or more layers, and the innermost resin layer of the sealant layer with the multilayer structure contains the additive.

COPYRIGHT: (C)2001,JPO

